

Fully Synthetic

Kixx ATF DX-III

Automatic Transmission Fluid

GM DEXRON®-III , MERCON®, ALLISON C-4



DESCRIPTION

Modern vehicle and transmission designs place increased stress on the automatic transmission fluid.

Kixx ATF DX-III is superior to any other past or currently ATF for uses in passenger car with automatic transmission. And It can be recommended for Automatic transmission with lock-up clutch. It provides a higher quality performance due in part by its oxidation resistance, low temperature fluidity, appropriate friction performance, high shear stability, and near sludge free operation.

APPLICATIONS

In accordance with the GM powertrain licensing requirements for the use of the DEXRON trademark, ATF DX-III may be recommended for use in automatic transmissions or other units, such as power-steering systems, industrial hydraulic systems and air compressors for which the service-fill product is specified as DEXRON II E, DEXRON II or DEXRON fluid.

Lock-up automatic transmissions

PERFORMANCE STANDARDS

Auto Maker	Specification	Auto Maker	Specification
GM	DEXRON®-II, IID, IIE DEXRON®-III, IIIH TASA	Mitsubishi	Diaqueen SP-II, SP-III, SP-IV Diaqueen AW Diaqueen J2
Ford	MERCON® WSS M2C 138CJ, 166H WSS M2C 922A1, 924A FNR5	Nissan	Matic Fluid C, D, J, K
Honda	ATF Ultra II ATF-Z1(except in CVTs)	Suzuki	ATF, ATF HP ATF 2326, ATF 2384K JWS 3309
Hyundai / Kia	SP-II, SP-III, SP-IV, SP-IV M JWS 3314 Red 1	Toyota	ATF D-II, D-III ATF T-III, T-IV
JASO	M315-2013 1A M315-2013 2A	Volvo	CE 97340
Allison	C-3 & C-4	VW	5HP (19FL, 24A) G 055 025 A2(JWS 3309) TL 521 62
		ZF	TE-ML 09, 11A, 11B

CUSTOMER BENEFITS

- Ensures long life-time
- Provides high foam stability.
- Provides high antirusting performance and lower sludge formation.
- Provides good start operation in cold climates thanks to its excellent low-temperature fluidity.
- Provides more stable friction property.

KEY PROPERTIES

Density, kg/L @15°C	0.841
Kinematic Viscosity, mm ² /s @ 40°C	33.5
Kinematic Viscosity, mm ² /s @ 100°C	7.02
Pour Point °C	-48
Flash Point °C	230
Brookfield Viscosity, cP @-20°C	980
Brookfield Viscosity, cP @-40°C	11,840
Package (Liters)	1, 4T, 18, 20, 200

UNIQUE SELLING POINT

