

Fully Synthetic



Kixx ATF Multi

Multi-vehicle Automatic Transmission Fluid

JASO 1A, GM DEXRON®-III, TOYOTA T-IV,
HYUNDAI SP-III/SP-IV

DESCRIPTION

High-performance, high-quality multi-vehicle fluid for automatic transmissions. (Applicable for slip controlled lock-up clutch)
Kixx ATF Multi is a specially formulated fluid designed to meet the requirements of a wide range of Automatic Transmission Specifications requiring SP-II, SP-III, DEXRON® III, MERCON®, Allison C-4, Toyota T-III and IV. In addition, it meets the requirements of European OEM's like ZF-TE-ML-11A/B, Volvo CE 97340, and MB, VW, BMW 4, 5 and 6-speed automatic transmission specifications. Kixx ATF Multi is a special blend of high quality base stocks with an advanced additives system for use as a Service-Fill.

PERFORMANCE STANDARDS

| Auto Maker | Specification | Auto Maker | Specification |
|------------------|---------------------------------|---------------|-------------------------------|
| VW / Audi | G 052 162 (ZF Lifeguardfluid 5) | Hyundai / Kia | Dex-II, SP-II |
| | G 055 025 A2 (JWS 3309) | | JWS 3314, JWS 9683 |
| | 5HP (ZF 5 HP 30) | | SP-III, SP-IV |
| Mercedes Benz | 5HP (18FL/19FL/24A) | Jaguar | ATF Red-1 |
| | TL 521 62 | | ATF 3403 JLM20238 |
| | MB 236.1, 236.2, 236.3 | | ATF 3403-M115 |
| BMW | MB 236.5, 236.6, 236.7 | JASO | ATF LT71141, ZF 5HP 24 |
| | MB 236.8, 236.9 | | M315-2013 1A |
| | 7045E, ETL-8072B | | M315-2013 2A |
| Ford | JWS 3309 (T-IV) | Mazda | ATF 3317 |
| | LT71141(ZF 5 HP 18FL/19FL/24A) | | ATF D-II, F-1, FZ |
| | FNR5 | | ATF M-III, M-V, N-1, S-1 |
| Fuso | WSS M2C138CJ, M2C166H | Mitsubishi | Diaqueen ATF PA |
| | WSS M2C 922A1, 924A | | Diaqueen AW |
| | MERCON® | | Diaqueen J2, J3, SK |
| GM | ATF-A4 | Nissan | Diaqueen SP-II, SP-III, SP-IV |
| | ATF-II | | Matic Fluid C, D, J |
| | ATF-SPIII | | Matic Fluid K, S |
| Honda | DEXRON®-II, IID, IIE | Porsche | ATF 3403-M115 |
| | DEXRON®-III, IIIH | | T-IV (JWS 3309) |
| | TASA | | ZF 5HP 19FL, 5HP 20, LT71141 |
| Chrysler / Dodge | GM9986195(Alsin AW, JWS 3309) | Subaru | ATF, ATF 5AT, ATF HP |
| | ATF Ultra II | | ATF 2326, ATF 2384K |
| | ATF-Z1(except in CVTs) | | ATF 3314, ATF 3317 |
| Isuzu | DW-1 | Suzuki | JWS 3309 |
| | Besco ATF-II | | ATF D-II, D-III, T-III, T-IV |
| | Besco ATF-III | | ATF WS |
| JEEP | ATF+3, +4 | ZF | all 3 & 4 speed transmission |
| | | | TE-ML 09A, 11A, 11B |
| | | Shell | 3403, M115, LA 2634 |
| | | Texaco | 7045-E, 8072B, N402 |

CUSTOMER BENEFITS

- Anti shudder protection.
- Oxidation and thermal stability
- Provides high foam stability.
- Provides good start operation in cold climates thanks to its excellent low-temperature fluidity.
- Provides more stable friction property.
- Use for most vehicles

KEY PROPERTIES

| | |
|---|---------------|
| Density, kg/L @15°C | 0.846 |
| Kinematic Viscosity, mm ² /s @ 40°C | 38.3 |
| Kinematic Viscosity, mm ² /s @ 100°C | 7.5 |
| Pour Point °C | -47 |
| Flash Point °C | 225 |
| Brookfield Viscosity, cP @-20°C | 1,300 |
| Brookfield Viscosity, cP @-40°C | 13,800 |
| Package (Liters) | 1,4,4T,20,200 |


UNIQUE SELLING POINT

High Quality Multi-Vehicle Fluid for Automatic Transmissions

Specially formulated fluid designed to meet the requirements of a wide range of Automatic Transmission Specifications

- Hyundai/Kia/Mitsubishi SP-II, SP-III
- GM DEXRON III, Ford MERCON,
- Toyota T, T-II, T-III, T-IV
- 4,5 Speed BMW, MB,VW,
- Allison C-4, JASO M315 Type 1A
- Voith/MAN Commercial ATs,
- Nissan Matic C,DJ
- Suzuki/Subaru ATF Oil, ZF TE-ML-14A
- Mazda ATF D-III, ATF M-3

Kixx ATF Multi is suitable for many OEM S/F



Kixx ATF Multi is a special blend of high quality base stocks with an advanced additives system