

Fully Synthetic

Kixx D1 RV

High Performance Engine Oil
ACEA C3-12, API SN/CF



DESCRIPTION

Kixx D1 RV is formulated with the latest VHVI (Very High Viscosity Index) synthetic base oil combined with additive technology that produce minimum sulfated ash, phosphorous and sulfur content to meet the requirement of low SAPS oil. Kixx D1 RV is suitable for passenger car mounted with gasoline or diesel engines, also suitable for SUV and Recreational Vehicle (RV).

Kixx D1 RV maintains the engine durability while helps in extending the life of Diesel Particulate Filter (DPF) and helps increase DPF performance by using additive of minimum sulfated ash contents. Kixx D1 RV also helps extend the life of after-treatment device such as Selective Catalytic Reduction (SCR) with the low phosphorous and sulfur content additive technology

APPLICATIONS

- SUV and RV equipped with DPF, SCR and other after-treatment system where an ACEA C3 performance engine oil is required.
- Light duty diesel passenger cars and gasoline direct injection engines.
- Passenger cars that require API SN performance.
- Vehicles that requires MB, BMW specification performance.

PERFORMANCE STANDARDS

- ACEA C3-12
- API SN/CF
- MB 229.31, 229.51 / VW 502.00, 505.01 / BMW LL-04 Recommended

KEY PROPERTIES

SAE Grade	5W-30
Density, kg/L @15°C	0.848
Kinematic Viscosity, mm ² /s @ 40°C	69.2
Kinematic Viscosity, mm ² /s @ 100°C	12.3
Viscosity Index	178
Pour Point °C	-42
Flash Point °C	228
Package (Liters)	5, 200